

중등 KBA 39



Oil Pattern Distance Forward Oil Total Tank Configuration 39 17.25 mL Only A Reverse Brush Drop Reverse Oil Total Tank A Conditioner 35 8.55 mL infinity Oil Per Board Volume Oil Total Tank B Conditioner 50 ul 25.8 mL infinity

	START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	50	14	3	148	0.0	5.9	5.9	7400
2	6L	6R	2	50	18	3	58	5.9	11.0	5.1	2900
3	8L	8R	2	50	18	3	50	11.0	16.1	5.1	2500
4	10L	10R	2	50	18	3	42	16.1	21.2	5.1	2100
5	12L	12R	2	50	18	3	34	21.2	26.3	5.1	1700
6	14L	14R	1	50	22	3	13	26.3	29.4	3.1	650
7	2L	2R	0	50	26	3	0	29.4	36.0	6.6	0
8	2L	2R	0	50	30	3	0	36.0	39.0	3.0	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	3	0	39.0	28.0	-11.0	0
2	13L	13R	3	50	18	3	45	28.0	20.4	-7.6	2250
3	11L	11R	3	50	18	3	57	20.4	12.8	-7.6	2850
4	9L	9R	3	50	18	3	69	12.8	5.2	-7.6	3450
5	2L	2R	0	50	14	3	0	5.2	0.0	-5.2	0
ı											

Cleaner Ratio Main Mix 5:1 Forward
Cleaner Ratio Back End Mix 5:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	MIddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.58	1.67	1.01	1.01	1.67	4.58



